

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name QCP-QCS-1

Product Description 500 µg/mL: K, P, Tl; 200 µg/mL: As, Hg, Pb; 100 µg/mL: Al, B, Ba, Be, Ca, Cd, Ce, Co, Cr, Cu, Fe, Li, Mg, Mn, Na, Ni, Se, Sr, V, Zn; 25 µg/mL: Ag

Contains Beryllium di(acetate)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals

Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Company

Inorganic Ventures
300 Technology Drive
Christiansburg, VA 24073
Phone: 1(800) 669-6799
Email: info@inorganicventures.com

1.4. Emergency telephone number

Chemtrec 1-800-424-9300 (North America)

Chemtrec +1 703-741-5970 (International)

Europe	See above
--------	-----------

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

*Classification according to
Regulation (EC) No. 1272/2008 [CLP]*

GHS

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Carcinogenicity	Category 1A - (H350)
Corrosive to metals	Category 1 - (H290)

2.2. Label elements

Product identifier
Contains Beryllium di(acetate)

**Signal word**

Danger

Hazard statements

H290 - May be corrosive to metals

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H350 - May cause cancer

H319 - Causes serious eye irritation

EUH071 - Corrosive to the respiratory tract

Precautionary Statements - EU (§28, 1272/2008)

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P234 - Keep only in original container

2.3. Other hazards

Other hazards

Toxic to aquatic life

No information available

SECTION 3: Composition/information on ingredients**3.1 Substances**

Chemical name	EC No. (Index No.)	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	REACH registration number
Nitric acid	231-714-2 (007-004-00-1) (007-030-00-3) (078-012-00-0)	7697-37-2	3.5	(EUH071) Skin Corr. 1A (H314) Ox. Liq. 3 (H272) Acute Tox. 3 (H331)	No data available
Beryllium di(acetate)	208-850-6 (004-002-00-2)	543-81-7	0.11278	Acute Tox. 3 (H301) Skin Irrit. 2 (H315) Skin Sens. 1 (H317) Eye Irrit. 2 (H319) Acute Tox. 2 (H330) STOT SE 3 (H335) Carc. 1B (H350i) STOT RE 1 (H372) Aquatic Chronic 2 (H411)	No data available
Copper	231-159-6 (029-026-00-0)	7440-50-8	0.01	Aquatic Chronic 2 (H411)	No data available

Full text of H- and EUH-phrases: see section 16**SECTION 4: First aid measures****4.1. Description of first aid measures****General Advice**

Immediate medical attention is required. Show this safety data sheet to the doctor in attendance.

Inhalation	Call a physician or poison control center immediately. Remove to fresh air. If breathing is difficult, give oxygen. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.
Skin Contact	Immediate medical attention is required. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Eye Contact	Immediate medical attention is required. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.
Ingestion	Immediate medical attention is required. Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth to an unconscious person.
Self-protection of the first aider	Use personal protective equipment as required. Avoid contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects	Burn. Difficulty in breathing.
--	--------------------------------

4.3. Indication of any immediate medical attention and special treatment needed

Notes to Physician	Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Do not give chemical antidotes. Asphyxia from glottal edema may occur. Marked decrease in blood pressure may occur with moist rales, frothy sputum, and high pulse pressure
---------------------------	---

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media

No information available

5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit. Use personal protection equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal Precautions

Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Ensure adequate ventilation. Use personal protective equipment as required. Do not get in eyes, on skin, or on clothing.

Advice for emergency responders

Ensure adequate ventilation.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Prevent product from entering drains. See Section 12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

See Section 12: ECOLOGICAL INFORMATION.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Ensure adequate ventilation.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended.

7.2. Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep container tightly closed in a dry and well-ventilated place.

7.3. Specific end use(s)**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Exposure Limits**

Chemical name	European Union	United Kingdom	France	Spain	Germany DFG	
Nitric acid 7697-37-2	STEL: 1 ppm; STEL: 2.6 mg/m³;	STEL: 1 ppm; STEL: 2.6 mg/m³;	STEL-VLCT (indicatif): 1 ppm; STEL-VLCT (indicatif): 2.6 mg/m³;	STEL (VLA-EC): 1 ppm; STEL (VLA-EC): 2.6 mg/m³;		
Beryllium di(acetate) 543-81-7		TWA: 0.002 mg/m³; STEL: 0.006 mg/m³;	TWA-VME (restrictif): 0.0006 mg/m³; inhalabl e fraction	TWA-(VLA-ED): 0.0002 mg/m³; S		
Copper 7440-50-8		TWA: 1 mg/m³; dust and mist TWA: 0.2 mg/m³; fume STEL: 0.6 mg/m³; fume STEL: 2 mg/m³; dust and mist	TWA-VME: 0.2 mg/m³; fume TWA-VME: 1 mg/m³; dust STEL-VLCT: 2 mg/m³; dust	TWA-(VLA-ED): 0.01 mg/m³; respirable fraction	TWA-MAK: 0.01 mg/m ³; II(2); respirable fraction	
Chemical name	Italy MDLPS	Portugal	Netherlands	Finland	Denmark	
Nitric acid 7697-37-2	STEL: 1 ppm; STEL: 2.6 mg/m³;	TWA (VLE-MP): 2 ppm; STEL (VLE-CD): 1 ppm; STEL (VLE-CD): 2.6 mg/m³;	STEL: 0.5 ppm; STEL: 1.3 mg/m³;	TWA: 0.5 ppm; TWA: 1.3 mg/m³; STEL: 1 ppm; STEL: 2.6 mg/m³;	STEL: 1 ppm; STEL: 2.6 mg/m³;	
Beryllium di(acetate) 543-81-7		STEL (VLE-CD): 0.01 mg/m³; pSk	Sk		TWA: 0.00002 mg/m³; STEL: 0.00004 mg/m³;	
Copper 7440-50-8		TWA (VLE-MP): 0.2 mg/m³; fume TWA (VLE-MP): 1 mg/m³; dust; mist	TWA: 0.1 mg/m³; inhalable	TWA: 0.02 mg/m³; respirable dust	TWA: 1.0 mg/m³; dust and powder TWA: 0.1 mg/m³; fume STEL: 2 mg/m³; dust and powder STEL: 0.2 mg/m³; fume	
Chemical name	Sweden	Austria	Switzerland	Poland	Norway	Ireland
Nitric acid	LLV: 0.5 ppm	TWA-TMW: 1 ppm;	TWA-MAK: 2 ppm;	TWA-NDS: 1.4	TWA: 2 ppm;	STEL: 1 ppm;

7697-37-2	LLV: 1.3 mg/m ³ Binding STLV: 1 ppm Binding STLV: 2.6 mg/m ³	TWA-TMW: 2.6 mg/m ³ ; STEL-KZGW: 1 ppm (); STEL-KZGW: 2.6 mg/m ³ (); Ceiling: 1 ppm; Ceiling: 2.6 mg/m ³ ;	TWA-MAK: 5 mg/m ³ ; STEL-KZGW: 2 ppm; STEL-KZGW: 5 mg/m ³ ;	mg/m ³ ; STEL-NDSch: 2.6 mg/m ³ ;	TWA: 5 mg/m ³ ; STEL: 4 ppm (value calculated); STEL: 10 mg/m ³ (value calculated);	STEL: 2.6 mg/m ³ ;
Beryllium di(acetate) 543-81-7		DS	TWA-MAK: 0.0006 mg/m ³ ; inhalable dust S			TWA: 0.0002 mg/m ³ ; STEL: 0.0006 mg/m ³ (calculated);
Copper 7440-50-8	LLV: 1 mg/m ³ LLV: 0.2 mg/m ³	TWA-TMW: 1 mg/m ³ ; inhalable fraction TWA-TMW: 0.1 mg/m ³ ; respirable fraction, smoke STEL-KZGW: 4 mg/m ³ (4 X 15 min); inhalable fraction STEL-KZGW: 0.4 mg/m ³ (4 X 15 min); respirable fraction, smoke	TWA-MAK: 0.1 mg/m ³ ; inhalable dust STEL-KZGW: 0.2 mg/m ³ ; inhalable dust	TWA-NDS: 0.2 mg/m ³ ;	TWA: 0.1 mg/m ³ ; fume TWA: 1 mg/m ³ ; dust STEL: 3 mg/m ³ (value calculated); dust STEL: 0.3 mg/m ³ (value calculated); fume	TWA: 0.2 mg/m ³ ; fume TWA: 1 mg/m ³ ; dusts and mists STEL: 2 mg/m ³ ; dusts and mists STEL: 0.6 mg/m ³ (calculated); fume

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/Face Protection Wear safety glasses with side shields (or goggles).

Hand Protection Impervious gloves.

Skin and Body Protection Impervious clothing. Boots. Chemical resistant apron.

Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn.

Environmental Exposure Controls Prevent product from entering drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	clear /BLUE-GRAY
Odor	Odorless
pH - VALUE 1	No data available
Melting point / melting range	No data available
Initial boiling point and boiling range	100 °C / 212 °F
Literary reference	
Vapor pressure @20 °C (kPa)	No data available
Relative vapor density	No data available
Relative Density	No data available
Specific gravity - VALUE 1	No data available
Water solubility	Miscible
Literary reference	
Partition coefficient: n-octanol/water	No data available

Autoignition temperature
Decomposition temperature
Dynamic viscosity - VALUE 1

No data available
No data available
No data available

Explosive properties
Oxidizing Properties

No information available
No information available

VOC content

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

10.3. Possibility of hazardous reactions

Hazardous polymerization

None under normal processing.

Hazardous Reactions

None under normal processing.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

Bases Cyanides

10.6. Hazardous decomposition products

Nitrogen oxides (NOx).

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute Toxicity****Product Information**

The product causes burns of eyes, skin and mucous membranes.

Inhalation

Causes burns. Corrosive to respiratory system. Inhaled corrosive substances can lead to a toxic edema of the lungs. Contact with moist mucous membranes of the respiratory system can cause caustic condition resulting in burns. Aspiration may cause pulmonary edema and pneumonitis.

Eye Contact

Causes burns.

Skin Contact

Causes burns.

Ingestion

Can burn mouth, throat, and stomach.

The following ATE values have been calculated for the mixture

ATEmix (oral) 88,668.20 mg/kg

ATEmix (inhalation-dust/mist) 10.83 mg/l

ATEmix (inhalation-vapor) 75.70 mg/l

Unknown acute toxicity

3.50001 % of the mixture consists of ingredient(s) of unknown acute toxicity.

3.50001 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

3.50001 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

3.50001 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

1E-05 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

1E-05 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Component Information**Skin corrosion/irritation**

No information available.

Serious eye damage/eye irritation

No information available.

Sensitization

No information available.

Mutagenic Effects

No information available.

Carcinogenic effects

Chemical name	European Union
Beryllium di(acetate)	Carc. 1B

Reproductive Toxicity

No information available.

STOT - single exposure

No information available.

STOT - repeated exposure

May cause disorder and damage to the. blood. Central nervous system. Nervous system. lungs. Respiratory system.

Target organ effects

Skin, Eyes, Respiratory system.

Aspiration hazard

No information available.

SECTION 12: Ecological information**12.1. Toxicity**

Contains 1E-05 % of components with unknown hazards to the aquatic environment

Chemical name	Algae/aquatic plants	Fish	Crustacea
Copper	EC50: 0.0426 - 0.0535mg/L (72h, Pseudokirchneriella subcapitata) EC50: 0.031 - 0.054mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 0.0068 - 0.0156mg/L (96h, Pimephales promelas) LC50: <0.3mg/L (96h, Pimephales promelas) LC50: =0.2mg/L (96h, Pimephales promelas) LC50: =0.052mg/L (96h, Oncorhynchus mykiss) LC50: =1.25mg/L (96h, Lepomis macrochirus) LC50: =0.3mg/L (96h, Cyprinus carpio) LC50: =0.8mg/L (96h, Cyprinus carpio) LC50: =0.112mg/L (96h, Poecilia reticulata)	EC50: =0.03mg/L (48h, Daphnia magna)

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Chemical name	Partition coefficient
Nitric acid	-2.3

12.4. Mobility in soil

Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

Chemical name	PBT and vPvB assessment
Nitric acid	Not PBT/vPvB
Copper	Not PBT/vPvB

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from Residues/Unused Products

Dispose of in accordance with federal, state and local regulations.

Contaminated Packaging

Do not reuse empty containers.

Other information

Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

IMDG

14.1. UN-No

UN3264

14.2. Proper shipping name

Corrosive liquid, acidic, inorganic, n.o.s

14.3. Transport hazard class(es)	8
14.4. Packing Group	III
Description	Not applicable
14.5. Marine Pollutant	None
14.6. Special Provisions	None
No information available in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Transport No information available

RID

14.1. UN-No	UN3264
14.2. Proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s
14.3. Transport hazard class(es)	8
14.4. Packing Group	III
Description	Not applicable
14.5. Environmental hazard	None
14.6. Special Provisions	None

ADR

14.1. UN-No	UN3264
14.2. Proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s
14.3. Transport hazard class(es)	8
14.4. Packing Group	III
Description	Not applicable
14.5. Environmental hazard	None
14.6. Special Provisions	None

ICAO

14.1. UN-No	UN3264
14.2. Proper Shipping Name	Corrosive liquid, acidic, inorganic, n.o.s
14.3. Hazard Class	8
14.4. Packing Group	III
Description	Not applicable
14.5. Environmental hazard	None
14.6. Special Provisions	None

IATA-DGR

14.1. UN-No	UN3264
14.2. Proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s
14.3. Transport hazard class(es)	8
14.4. Packing Group	III
Description	Not applicable
14.5. Environmental hazard	None
14.6. Special Provisions	None

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

International Inventories

All of the components in the product are on the following inventory lists: U.S.A. (TSCA), Europe (EINECS/ELINCS/NLP), Canada (DSL/NDSL), Philippines (PICCS), Japan (ENCS), China (IECSC), Australia (AICS), Korea (ECL).

TSCA	Complies
EINECS/ELINCS	Complies
DSL/NDSL	Complies

PICCS	Complies
ENCS	Complies
IECSC	Complies
AIIC	Complies
KECL	Complies

Legend

EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

PICCS - Philippines Inventory of Chemicals and Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

AICS - Australian Inventory of Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

15.2. Chemical safety assessment

No information available

SECTION 16: Other information**Full text of R-phrases referred to under sections 2 and 3**

No information available

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

EUH071 - Corrosive to the respiratory tract

H272 - May intensify fire; oxidizer

H301 - Toxic if swallowed

H314 - Causes severe skin burns and eye damage

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H330 - Fatal if inhaled

H331 - Toxic if inhaled

H335 - May cause respiratory irritation

H350i - May cause cancer by inhalation

H372 - Causes damage to organs through prolonged or repeated exposure

H411 - Toxic to aquatic life with long lasting effects

Revision date 27-Feb-2026

Reason for Revision Not applicable.

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet